

Connection Box for Mains Plug

	Box A2/6600-p P 6600U	Box A2/6600-i IS 6600H, IS 6680H	Box A2/6600-s KT 6680U, S 6600U	Box A2/6600-k KT 6780H, S 6700U
Mains connection	For DUT with ground bond connection (protection class I) via socket			
Connection via	Banana plug (4 mm 0.6 in) / High-voltage plug (ST 14)			
Connection cable	1,5 m 59.0 in			
Material	PVC box			
Socket selection Type	B, E, G, I, J, L			
Dimensions Mounting plate (approx.)	Width: 81 mm 3.2 in – Depth: 113 mm 4.4 in			
Dimensions (approx.)	Height: 58 mm 2.3 in – Width: 81 mm 3.2 in – Depth: 82 mm 3.2 in			

	Box A3/6600-p P 6600U	Box A3/6600-i IS 6600H, IS 6680H	Box A3/6600-s KT 6680U, S 6600U	Box A3/6600-k KT 6780H, S 6700U
Mains connection	For DUT with ground bond connection (protection class I) via universal socket outlet PP 66			
Connection via	Banana plug (4 mm 0.6 in) / High-voltage plug (ST 14)			
Connection cable	1,5 m 59.0 in			
Material	PVC box			
Universal socket	Australia, Brazil, China, Great Britain, Italy, Switzerland, USA			
Dimensions Mounting plate (approx.)	Width: 81 mm 3.2 in – Depth: 113 mm 4.4 in			
Dimensions (approx.)	Height: 58 mm 2.3 in – Width: 81 mm 3.2 in – Depth: 82 mm 3.2 in			

	Box A4/6600-i IS 6600H, IS 6680H	Box A4/6600-s KT 6680U, S 6600U	Box A4/6600-k KT 6780H, S 6700U
Mains connection	For DUT without ground bond connection (protection class II) via universal socket outlet PP 20 High-voltage socket BU 02 for connecting a high-voltage test probe SP 02		
Connection via	Banana plug (4 mm 0.6 in) / High-voltage plug (ST 14)		
Connection cable	1,5 m 59.0 in		
Material	PVC box		
Universal socket	Australia, Austria, Brazil, China, Denmark, Germany, Great Britain, Hungary, Italy, Netherlands, New Zealand, Poland, Portugal, Spain, Sweden, Switzerland, Turkey, USA		
Dimensions Mounting plate (approx.)	Width: 81 mm 3.2 in – Depth: 113 mm 4.4 in		
Dimensions (approx.)	Height: 58 mm 2.3 in – Width: 81 mm 3.2 in – Depth: 82 mm 3.2 in		

	Box A9/6600-s KT 6680U, S 6600U	Box A9/6600-k KT 6780H, S 6700U
Mains connection	For DUT with ground bond connection (protection class I) via 3 manual terminals	
Connection via	Banana plug (4 mm 0.6 in) / High-voltage plug (ST 14)	
Connection cable	1,5 m 59.0 in	
Dimensions (approx.)	Height: 50 mm 1.9 in – Width: 60 mm 2.4 in – Depth: 130 mm 5.1 in	